

CONTROL / CONTROL RED

KFE / KFE RED SKYLIGHT



APPLICABLE

- In public and domestic buildings
- In unheated, uninhabited spaces like attics, garages, etc.
- In roof pitch range of 15-60° (KFE 8585: 15-45°)
- Suitable for all common roofing material, up to 90 mm profile height

FEATURES













- Opening restrictor
- The sash can be fixed in 90° open position
- Preinstalled flashing with apron
- Preinstalled foam collar for roofing connection
- Weather and UV resistant
- 14 mm double insulating glazing [3-8-3]
- Galvanized steel handle with two ventilation positions
- 5 years guarantee
- Simple and quick installation

MATERIAL

- Frame: Kiln-dried, FSC certified pine wood
- Fungicide protection
- Aluminium sash profile
- Lead-free, double layer, easy to shape bottom apron
- Available colour variants:
 - Grey RAL 7043 (KFE series)
 - Red RAL 8004 (KFE RED series)

AVAILABLE SIZES [CM]



				
Product type	KFE 4555 KFE 4555 RED	KFE 4573 KFE 4573 RED	KFE 6565 KFE 6565 RED	KFE 8585
Size**	45 x 55	45 x 73	65 x 65	85 x 85
Opening options	*  	*  	*  	*  

* Factory default opening

** Given sizes refer to the external dimensions of the wooden frame



www.dakea.com

