

GOOD PVC OPAQUE

KPV CENTER PIVOT PVC ROOF WINDOW



VARIANT	B3300
PANE	
Construction	4-16-4H
Double glazing	24 mm
Low E	✓
Gas	Argon
Toughened	✓
U_g (W/m ² K)	1.1
Total solar energy transmittance	NPD*
WINDOW	
U_w (W/m ² K)	1.4
Water tightness	E1500
Air permeability	Class 4
Resistance to wind load	Class C4*
Sound reduction	32 [-1,-3] dB
Ventilation valve	✓
COLOUR	
White	✓

* NPD: No Performance Determined



NEXT 20
GUARANTEE



MAX PROTECT

APPLICABLE

- In public and domestic buildings
- In heated, inhabited rooms
- In roof pitch range of 15-90°
- Suitable on all common roofings with proper flashing

FEATURES

- Centre pivot
- Obscure glass
- Extra sliding gasket
- Toughened outer glass
- Ventilation valve
- Two passive ventilation positions via handle
- Easy installation

MATERIAL

- EASY-CLEAN PVC - Lead free PVC
- Polystyrene insulation insertion
- Steel reinforcement

COVER PARTS

- Aluminium, lacquered, RAL 7043

HANDLE

- New, ergonomically designed moulded zinc handle, lacquered

HINGE

- Centre pivot



TECHNICAL SPECIFICATION

MEASURES [cm]								
CODE	NOMINAL SIZE	FRAME EXTERNAL SIZE		PANE SIZE		VISIBLE GLASS		
		WIDTH	HEIGHT	WIDTH	HEIGHT	WIDTH	HEIGHT	EFFECTIVE LIGHT AREA m ²
KPV C2A	55 x 78	55	77.8	39.8	64.9	37.3	59	0.220
KPV C4A	55 x 98	55	97.8	39.8	84.9	37.3	79	0.295
KPV C6A	55 x 118	55	117.8	39.8	104.9	37.3	99	0.369
KPV F6A	66 x 118	66	117.8	50.8	104.9	48.3	99	0.478
KPV M4A	78 x 98	78	97.8	62.8	84.9	60.3	79	0.476
KPV M6A	78 x 118	78	117.8	62.8	104.9	60.3	99	0.597

FLASHING COMPATIBILITY TABLE (ACCORDING TO PROFILE HEIGHT OF ROOFING MATERIAL)							
SIZE CODE	SLATE with one-piece side element 0-16 mm (2x8 mm)	INTERLOCKING FLAT TILE (16-50 MM)	TILE (16-50 mm)	UNIVERSAL (16-120 mm)	UNIVERSAL for 18 mm TWIN combi (16-120 mm)	COMBI Universal (16-120 mm)	COMBI Slate 0-16 mm (2x8mm)
C2A	KLS C2A	KFT C2A	KTF C2A	KUFC2A	-	•	•
C4A	KLS C4A	KFT C4A	KTF C4A	KUFC4A	UBX C4A 18	•	•
C6A	KLS C6A	KFT C6A	KTF C6A	-	UBX C6A 18	•	•
F6A	KLS F6A	KFT F6A	KTF F6A	KUF F6A	-	•	•
M4A	KLS M4A	KFT M4A	KTF M4A	KUFM4A	UBX M4A 18	•	•
M6A	KLS M6A	KFT M6A	KTF M6A	KUFM6A	UBX M6A 18	•	•

Please check the necessary combi flashings according to the installation.

BLIND COMPATIBILITY TABLE					
SIZE CODE	BLACKOUT	ROLLER	ANTI HEAT	VENETIAN	
C2A	DUA C2A	RHA CXA	MIA CXA	PAA C2A	
C4A	DUA C4A	RHA CXA	MIA CXA	PAA C4A	
C6A	-	-	-	-	
F6A	DUA F6A	RHA FXA	MIA FXA	PAA F6A	
M4A	DUA M4A	RHA MXA	MIA MXA	PAA M4A	
M6A	DUA M6A	RHA MXA	MIA MXA	PAA M6A	

PANE 33
Heat reflecting and Energy saving,
obscure insulated glass
4-16-4H

U_g: 1,1 W/m²K
U_w: 1,4 W/m²K

4 mm obscure float glass

16 mm spacer

Argon gas filled cavity

Low-E coating [reflects heat]

4 mm toughened safety glass

AVAILABLE SIZES [cm]

C2A	C4A	C6A	F6A	M4A	M6A
55x78	55x98	55x118	66x118	78x98	78x118

CE¹⁸
EN 14351-1:2006
+A2:2016

www.dakea.com

