

SOLAR ROLLER SHUTTER

SSR



Operation with
solar energy



Extra heat and noise
protecting lamels



Factory-paired
wall switch

3 YEAR
GUARANTEE

APPLICABLE

- In public and domestic buildings
- In roof pitch range of 15-90°
- Designed to perfectly fit to Dakea windows regardless the roofing material
- Not suggested for recessed installation

FEATURES

- The most effective solution against solar heat
- Excludes light completely
- Protects against burglary
- Gives you 100% privacy
- Ready-to-use solution, no additional work is needed
- io-homecontrol® compatible
- Fully charged battery is able to manage 100 open and close cycles

MATERIAL




- Coated aluminium
- Double insulated aluminum slats for increased insulation and noise cancellation

OPERATION

- Electrical operation 24V 4-step tubular motor
- Factory paired wall switch is able to operate up to 200 shutters simultaneously
- The shutter follows the movement of the sash whether the panzer is up or down
- More shutter can be controlled with one wall switch
- Solar shutter is not compatible with high-pivot windows (KHV, MOE, MOEVX)

AVAILABLE SIZES [CM]

C2A	C4A	C6A	F4A	F6A	M4A	M6A	M8A	M10A	P6A	P8A	P10A	S6A	S8A	U4A	U8A
55x78	55x98	55x118	66x98	66x118	78x98	78x118	78x140	78x160	94x118	94x140	94x160	114x118	114x140	134x98	134x140



EN 14351-1:2006
+A2:2016

www.dakea.com

