

# CONTROL SYSTEM OVERVIEW

## FOR SMOKE VENT WINDOW

		
<p><b>CONTROL UNIT</b> <b>KFC305</b></p> <ul style="list-style-type: none"> <li>• 24 volt output voltage, 5 amp</li> <li>• Control unit for 1 or 2 KAS smoke ventilation roof windows</li> <li>• CE-marked in compliance with EN 12101-10.</li> <li>• Conforms to ISO 21927-9:2012</li> <li>• Integrated emergency power supply for 72 hours.</li> <li>• Dimensions: 238 x 286 x 113 mm (W x H x D).</li> <li>• Possible to connect up to 35 control units via BUS communication, allowing control of up to 70 KAS smoke ventilation windows.</li> <li>• In installations where a third-party control is used, KFC 305 can be used as a power supply only for the connected KAS smoke ventilation window(s).</li> <li>• Colour: White front with black indication panel</li> </ul>	<p><b>CONTROL UNIT</b> <b>KFC310</b></p> <ul style="list-style-type: none"> <li>• 24 volt output voltage, 10 amp.</li> <li>• Control unit for 3 - 4 KAS smoke ventilation roof windows</li> <li>• CE-marked in compliance with EN 12101-10.</li> <li>• Conforms to ISO 21927-9:2012</li> <li>• Integrated emergency power supply for 72 hours.</li> <li>• Dimensions: 238 x 286 x 113 mm (W x H x D).</li> <li>• Possible to connect up to 35 control units via BUS communication, allowing control of up to 140 KAS smoke ventilation windows.</li> <li>• In installations where a third-party control is used, KFC 310 can be used as a power supply only for the connected KAS smoke ventilation window(s).</li> <li>• Colour: White front with black indication panel</li> </ul>	<p><b>BREAK-GLASS POINT</b> <b>KFK300</b></p> <ul style="list-style-type: none"> <li>• Break-glass point for activation smoke ventilation function</li> <li>• Dimensions: 125 x 125 x 38 mm (W x H x D)</li> <li>• Visual and acoustic indication of correct function, error, and alarm.</li> <li>• Colour: Grey</li> </ul>
		
<p><b>COMFORT SWITCH</b> <b>KFK200</b></p> <ul style="list-style-type: none"> <li>• Wall switch enabling natural ventilation for daily comfort</li> <li>• Dimensions: 81 x 81 x 12 mm (W x H x D).</li> <li>• Up to 10 wall switches can be used with each KFC 210/220 control unit.</li> <li>• Colour: White (RAL 1013)</li> </ul>	<p><b>SMOKE DETECTOR</b> <b>KFA100</b></p> <ul style="list-style-type: none"> <li>• Smoke detector for early fire detection</li> <li>• Dimensions (including socket): 50 x 100 mm (H x W)</li> <li>• Up to 10 smoke detectors can be used with KFC 210/220 control unit</li> <li>• Colour: White (RAL 9003)</li> <li>• Visual indication of activation</li> </ul>	<p><b>RAIN SENSOR</b> <b>KLA200</b></p> <ul style="list-style-type: none"> <li>• Closes window in comfort ventilation mode in case of rains.</li> <li>• Overruled in the event of fire.</li> <li>• Dimensions: 40 x 70 x 13 mm (W x H x D)</li> <li>• Colour: Dark grey (NCS S 7500-N).</li> </ul>



# STAIRCASE SYSTEM SKETCH

